

K990



➔ Standalone RFID Time & Attendance with Access Control

Card Capacity : 30,000
 Transaction Storage : 1,00,000
 Card Reader : Yes
 CPU : 32 bit Microprocessor - 800Mhz
 FAR : $\leq 0.0001\%$ / FRR : $\leq 1\%$
 Identification Speed : ≤ 0.1 sec
 Display : 3.5" TFT
 Keypad : 4 x 4 with 5 function Keys
 Schedule Bell/Speaker : Mini Speaker
 Communication : RS232/485, TCP/IP
 Push data : Yes
 Standard Features : Work code, SMS, DLST,
 Self service query, Status Switch
 Power Supply : 12V DC , 1.5Amp
 Operating Temperature : 0°C to 45°C
 Operating Humidity : 20% -80%
 Dimension : 212 x 159 x 45 mm
Access Control : Wiegand : In & Out
 both 26 or 34 bit (With or without site code)

Relay : 12 V relay for lock EM lock,
 Bolt Lock or Strike lock
 Support Fire Alarm : Yes / Door Sensor ; Yes
 Anti Passback : Yes / Door Bell : Yes
 Support exit reader : KR 500E, KR503, 101HE and
 50 time zones, 5 group, 10 time combination
 Battery : Yes / Card Readers : Yes
 Communication : GPRS, Wifi (Optional)
 Printer : Yes

Compatibility :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)

Compatible Software & SDK :

- Smart office suite desktop and web
- Etime track lite desktop & web
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data. Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications