



Multibio 800

➔ Multi-biometric Access Control and Time Attendance System

Face capacity : 400(1:N)
Fingerprints templates : 1000
Card Storage : 1000
Transaction storage : 1,00,000
Card reader : Yes
CPU : 800 Mhz 32 bit Microprocessor
Fingerprint sensor : 500 DPI Optical sensor
FAR : $\leq 0.0001\%$
FRR : $\leq 1\%$
Identification speed : < 0.5 sec
Algorithm Ver : 10
Display : 2.8 inch TFT LCD Color Screen
LED Indicator : Green/Red
Schedule Bell/Speaker : Mini Speaker
Communication : TCP/IP, RS232/485, USB Host
Push data : Yes
Power Supply : 12V DC, 3A
Operating Temperature : 0 °C - 45 °C
Operating Humidity : 20% - 80%
Wiegand : Yes

Relay : 12 V relay for lock EM lock, Bolt Lock or Strike lock

Support Fire Alarm : Yes

Door Sensor : Yes

Anti Passback : Yes

Door Bell : Yes

Support exit readers : F12

Battery : No | Communication : No

Sensor : No

Compatible :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)

Compatible Software and SDK:

- Smart office suite desktop and web
 - etime track lite desktop & web
 - SDK for desktop applications
 - Web based Device Manager/ePush server using Push data.
- Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications