



Multibio 700

➔ Multi-biometric Identification Time Attendance & Access Control System

Fingerprint Templates : 2000
Face Capacity : 1500
Card Capacity : 10,000
Transaction storage : 1,00,000
Card Reader : Yes
Push Data : Yes
Image Sensor : Special Sterio Dual Sensor
FAR : $\leq 0.0001\%$ / FRR : $\leq 1\%$
Identification Speed : ≤ 1 Sec
Algorithm Ver : 10
Display : 3" Touch Screen
Keypad : 2 Function Keys
Schedule Bell/Speaker : Mini Speaker
Communication : RS232/485, TCP/IP, USB-Host
Camera : High Resolution Infrared Camera
Standard Features : ID Card, Automatic Status Switch, Self Service Query Work code
Power Supply : 12V DC, 1.5 Amps
Operating Temperature : 0°C to 45°C
Operating Humidity : 20% -80%
Dimension : 195 x 100 x 275 mm

Access Control :

Wiegand : Both 26 & 32 Bit In and Out
Relay : 12 V
Support Fire Alarm : Yes / Door Sensor : Yes
Anti Passback : No / Door Bell : Yes
Support exit reader : KR 500, 101 HE
Battery : No / Card Readers : Yes
Communication : No
Printer : No

Compatibility :

- 3rd party electric lock, Door sensor, Exit button

Compatible Software & SDK :

- Smart office suit Desktop
- etime track lite Desktop
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications